

NEW FROM POLYPIPE FLOOR HEATING SYSTEMS:

TOUCH SCREEN PROGRAMMABLE ROOM THERMOSTAT



The market leading floor heating range from Polypipe has been further enhanced with our touch screen programmable room thermostats. Available in white or silver, these feature rich thermostats deliver outstanding functionality with contemporary touch screen operation and all at a highly competitive price.

The range is perfect for all new floor heating installations but is also an ideal solution for upgrading existing customer systems.

KEY FEATURES:

- Available in white or silver to match light fittings and room décor
- High visibility blue backlight
- On screen display shows current status and programme
- Allows 3 separate temperature settings per day:
 - Comfort
 - Economy
 - Night
- Programming options for 7 day week or 5+2 working week/weekend modes
- Includes override, holiday, frost and alarm features
- Compatible with existing controls and wiring centre (PB4ZM)



Visit www.ufch.com or call 01709 770000 for more information



 **Polypipe**

NEW FROM POLYPIPE FLOOR HEATING SYSTEMS:

TOUCH SCREEN PROGRAMMABLE ROOM THERMOSTAT

Each touch screen thermostat can be used in conjunction with or in lieu of existing Polypipe programmable thermostats. This enables floor heating customers to choose a more aesthetic option in some or all rooms.

The touch screen products are fully compatible with the existing wiring centre and can be offered as an upgrade or retrofitted to existing systems.

	PRODUCT CODE	PRICE
	PBTSPW	£120.00
	PBTSPS	£120.00

TECHNICAL DATA

Dimension H x L x W (mm)	87 x 135 x 32
Operating Voltage	2 Batteries 1.5v LR6/AA
Temperature Control Range	+5°C / +35°C
Temperature Display Range	+5°C / 37°C
Switching Capacity (Changeover Contact) at Ohmic Loads	Max 6a 240v 50hz
at inductive loads $\cos \Phi = 0.6$	Max 2a 240v 50hz
Switching Output	Floating
Function Modes	Heat / Cool
Anti-Frost	+7°C
Ambient Temperature	-5°C / +45°C
Programming	Daily, Weekly and 5/2
Class of Protection	II
Index of Protection	IP20
Displayed Temperature Update	10s
Reading Accuracy	+/-1°C at 20°C
Reading Resolution	+/-0.1°C
Swing	0.2°C
Comply with EMC and LV directives LVD: EN60730-1, EN60730-2-7, EN60730-2-9 EMC: EN55014-1, EN55014-2, EN61000-3-2, EN61000-3-3	

Subject to technical modifications



POLYPIPE PLC
Broomhouse Lane
Edlington
Doncaster
DN12 1ES



Visit www.ufch.com or call 01709 770000 for more information

 **Polypipe**