

Waste

EN1451-1	Polypropylene push-fit waste pipe and fittings (BS5254)
EN1455-1	ABS Solvent weld waste pipe and fittings (BS5255)
EN1566-1	PVC-mu waste pipes (BS5255)
EN1329-1	PVC-mu fittings (BS5255)
BS394	Waste traps

Waste

Generally speaking the choice of a waste product joint system is down to personal preference. Both compression and push fit waste systems allow flexibility in the installation process because of their mechanical nature. A solvent weld system, ABS or MuPVC may be used where the installer / client requires a homogenous joint in, especially in areas such as boxings and ducts. The MuPVC system has a higher temperature resistance than other materials and is also more resistant to UV light for outdoor applications.

32mm	Push-fit Waste (PP)	Black/White/Brown/Grey
40mm	Push-fit Waste (PP)	Black/White/Brown/Grey
50mm	Push-fit Waste (PP)	Black/Grey
32mm	Solvent Waste (ABS)	Black/White/Grey/Brown
40mm	Solvent Waste (ABS)	Black/White/Grey/Brown
50mm	Solvent Waste (ABS)	Black/White/Grey
32mm	Solvent Waste (MuPVC)	White/Solvent Grey/Black
40mm	Solvent Waste (MuPVC)	White/Solvent Grey/Black
50mm	Solvent Waste (MuPVC)	White/Solvent Grey/Black
32mm	Compression Waste (MuPVC)	White
21.5mm	Compression Waste (MuPVC)	White
21.5mm	Push-fit Overflow(MuPVC)	Grey
40mm	Solvent Overflow (PVCu)	White
32 & 40mm	Traps (PP)	White

The darker Solvent Grey has been introduced for Solvent Soil and MuPVC Waste Systems only